



HYDROTAP G5 BCS CLASSIC PLUS GUNMETAL



BOILING



CHILLED



SPARKLING

FILTERED

Order Code H55783Z09AU

Zip HydroTap Classic Plus Boiling, Chilled, Sparkling, Filtered water tap features simple, intuitive controls including continuous flow to fill bottles, Boiling water safety lock, and antimicrobial protection impregnated within the new Classic Plus touch-pad for enhanced hygiene. The water system features a single under bench command centre including full colour interactive touch screen display with pin code protection and customisable settings including 2 boiling water safety modes, 3 energy saving modes including ON/OFF timers and sensor activated 'sleep when it's dark', 'Quiet' mode with automated intelligent fan speed adjustment, antimicrobial protection impregnated into key water paths for enhanced hygiene, 100% water efficient air cooled technology, 0.2 micron water filtration, and 2 disposable CO2 cylinders.



Manufacturing Code H55783Z09AU

Capacity Residential

Tap Zip HydroTap CLASSIC PLUS Tap (Gunmetal)

Water Pressure Min 250kPa - Max 700kPa

Water Connection 1/2" BSP (G1/2)

Water Supply Requirements Cold

Water Valves Integrated 500kPa Pressure limiting valve and Dual Check Valve

Power Rating 1.53kW 220-240V 50Hz

Power Supply 1 x 10 Amp socket outlet

Dimensions W339mm x D483mm x H333mm

Product Approvals WaterMark, RCM, ARC

Installation Requirements

1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations.
2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1.5 metres of the product.
3. Discrete cabinetry cut outs are required for airflow. 40mm minimum clearance on cupboard base overhang required otherwise alternative installation options are available.
4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service.
5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit.
6. Installation by Zip Professional Service can be arranged with a phone call or through www.zipwater.com/book-service-visit

Installation Detail

8K12 HydroTap G5 v.1.11.10.2024 BCS BCS20

Ventilation requirements

Contact your local service provider if ventilation is not suitable

Option 1. Cupboard with 40mm min overhang

40mm min
50mm min clearance beside inlet

Air exhaust cut-out
min. 40
300

Option 2. Cupboard with less than 40mm overhang

50mm min clearance beside inlet

Floor mounting plate cut-out
40
300

Air exhaust cut-out
60
285

HydroTap Tap options

Classic Plus

Elite Plus

Raised Font with 135mm Extension
Part No. 95258

Cutting detail

Tap Positioning

Position the Tap to dispense into the sink. Alternatively, mount on a Font, available as an accessory.

○ Ø35mm hole for Tap

Sink

Clearance Envelope

4mm buffer pad air space

200 min.
333
339
50 min.
380
483

Mains cold water isolation valve (not supplied)

IEC Flex & Plug 230-240V, 50Hz power outlet

CO₂ gas cylinder

Ø105

A minimum overhang or kickboard height is required for ventilation. Refer to the installation instructions.

HydroTap G5

BCS Home

shown with Classic Plus tap and Raised Font (optional accessory)