



# HYDROTAP G5 BC CLASSIC PLUS MATTE BLACK



BOILING

CHILLED

FILTERED

## Order Code H55784Z03AU

Zip HydroTap Classic Plus Boiling, Chilled, Filtered water tap features simple, intuitive controls including continuous flow to fill bottles, Boiling water safety lock, and antimicrobial protection impregnated within the new Classic Plus touch-pad for enhanced hygiene. The water system features a single under bench command centre including full colour interactive touch screen display with pin code protection and customisable settings including 2 boiling water safety modes, 3 energy saving modes including ON/OFF timers and sensor activated 'sleep when it's dark', 'Quiet' mode with automated intelligent fan speed adjustment, antimicrobial protection impregnated into key water paths for enhanced hygiene, 100% water efficient air cooled technology, and 0.2 micron water filtration.



Manufacturing Code H55784Z03AU

Capacity Residential

Tap Zip HydroTap CLASSIC PLUS Tap (Matte Black)

Water Pressure Min 170kPa - Max 700kPa

Water Connection 1/2" BSP (G1/2)

Water Supply Requirements Cold

Water Valves Integrated 500kPa Pressure limiting valve and Dual Check Valve

Power Rating 1.44kW 220-240V 50Hz

Power Supply 1 x 10 Amp socket outlet

Dimensions W280mm x D478mm x H333mm

Product Approvals WaterMark, RCM, ARC

## Installation Requirements

1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations.
2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1.5 metres of the product.
3. Discrete cabinetry cut outs are required for airflow. 40mm minimum clearance on cupboard base overhang required otherwise alternative installation options are available.
4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service.
5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit.
6. Installation by Zip Professional Service can be arranged with a phone call or through [www.zipwater.com/book-service-visit](http://www.zipwater.com/book-service-visit)

## Installation Detail

8X12 HydroTap G5 v.11.10.2024 BC BC20

### Ventilation requirements

Contact your local service provider if ventilation is not suitable

#### Option 1. Cupboard with 40mm min overhang

50mm min clearance beside inlet

Air exhaust cut-out

min. 40

240

#### Option 2. Cupboard with less than 40mm overhang

50mm min clearance beside inlet

Floor mounting plate cut-out

Air exhaust cut-out

40

240

60

285

### HydroTap Tap options

**Classic Plus**

**Elite Plus**

### Tap Positioning

Position the Tap to dispense into the sink. Alternatively, mount on a Font, available as an accessory.

Ø35mm hole for Tap

Sink

### Clearance Envelope

200 min.

333

280

50 min.

IEC Flex & Plug 230-240V, 50Hz power outlet

Mains cold water isolation valve (not supplied)

### 4mm buffer pad air space

4mm buffer pad air space

### Clearance Envelope

478

260

116

164

A minimum overhang or kickboard height is required for ventilation. Refer to the installation instructions.

### Raised Font with 135mm Extension Part No. 95258

351

260

116

268

20

### Cutting detail

ø10 for M6 stud

ø86 hole for bowl

ø35 hole for tap

152

## HydroTap G5

### BC Home

shown with Classic Plus tap and Raised Font (optional accessory)