



HYDROTAP G5 BC CUBE PLUS BRUSHED NICKEL



BOILING

CHILLED

FILTERED

Order Code H5C784Z11AU

Zip HydroTap Design Range Boiling, Chilled, Filtered water tap features a single under bench command centre including full colour interactive touch screen display with pin code protection and customisable settings including boiling water safety mode, 3 energy saving modes including ON/OFF timers and 2 hour sleep mode, 'Quiet' mode with automated intelligent fan speed adjustment, antimicrobial protection impregnated into key water paths for enhanced hygiene, 100% water efficient air cooled technology, and 0.2 micron water filtration.



Manufacturing Code H5C784Z11AU

Capacity Residential

Tap Zip HydroTap Design Range CUBE Plus Tap (Brushed Nickel)

Water Pressure Min 170kPa - Max 700kPa

Water Connection 1/2" BSP (G1/2)

Water Supply Requirements Cold

Water Valves Integrated 500kPa Pressure limiting valve and Dual Check Valve

Power Rating 1.44kW 220-240V 50Hz

Power Supply 1 x 10 Amp socket outlet

Dimensions W280mm x D478mm x H333mm

Product Approvals WaterMark, RCM, ARC

Warranty 5 years (appliance warranty 36 months plus additional 24 months tank warranty)

Installation Requirements

1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations.
2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1.5 metres of the product.
3. Discrete cabinetry cut outs are required for airflow. 40mm minimum clearance on cupboard base overhang required otherwise alternative installation options are available.
4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service.
5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit.
6. Installation by Zip Professional Service can be arranged with a phone call or through www.zipwater.com/book-service-visit

Installation Detail

BK12 HydroTap G5 v1.11.10.2024 IBC BC20

Ventilation requirements

Contact your local service provider if ventilation is not suitable

Option 1. Cupboard with 40mm min overhang

50mm min clearance beside inlet

Air exhaust cut-out

min. 40

240

Option 2. Cupboard with less than 40mm overhang

50mm min clearance beside inlet

Floor mounting plate cut-out

40

240

Air exhaust cut-out

40

285

HydroTap Tap options

HydroTap Arc Plus Tap

HydroTap Cube Plus Tap

Tap Positioning

Position the Tap to dispense into the sink. Alternatively, mount on a Font, available as an accessory.

Ø35mm hole for Tap

Sink

HydroTap Arc Plus

Clearance Envelope

200 min.

333

Mains cold water isolation valve (not supplied)

IEC Flex & Plug 230-240V, 50Hz power outlet

280

50 min.

4mm buffer pad air space

Clearance Envelope

A minimum overhang or kickboard height is required for ventilation. Refer to the installation instructions.

478

Standalone Font

shown with Arc Plus Tap

Cutting detail

174 for HydroTap Arc/Cube

3-off, Ø10 holes @ 155mm PCD, equispaced

Ø140 hole for bowl

Ø176 outline of Font

Ø35 hole for tap

HydroTap G5 BC Home

shown with HydroTap Arc Plus and Standalone Font (optional accessory)

SCALE 1:5
ALL DIMENSIONS IN MM UNLESS OTHERWISE SPECIFIED. INSTALLATION DIAGRAMS ARE FOR ILLUSTRATIVE PURPOSES ONLY. HOSES ARE NOT SHOWN TO SCALE AND CANNOT BE LENGTHENED.