




## HydroTap G5 BCS Classic Plus Brushed Gunmetal

Boiling Chilled Sparkling

 **Finish:** Brushed Gunmetal

**Product code:** H55783Z19AU

**Capacity:** Residential

Zip HydroTap Classic Plus Boiling, Chilled, Sparkling, Filtered water tap features simple, intuitive controls including continuous flow to fill bottles, Boiling water safety lock, and antimicrobial protection impregnated within the new Classic Plus touch-pad for enhanced hygiene. The water system features a single under bench command centre including full colour interactive touch screen display with pin code protection and customisable settings including 2 boiling water safety modes, 3 energy saving modes including ON/OFF timers and sensor activated 'sleep when it's dark', 'Quiet' mode with automated intelligent fan speed adjustment, antimicrobial protection impregnated into key water paths for enhanced hygiene, 100% water efficient air cooled technology, 0.2 micron water filtration, and 2 disposable CO2 cylinders.

# Specifications

|                     |   |
|---------------------|---|
| Product name        | HydroTap G5 BCS Classic Plus Brushed Gunmetal                                       |
| Product code        | H55783Z19AU   |
| Filtered water type | BCS   |
| Product approvals   | WaterMark, RCM, ARC   |
| Warranty            | 3-years comprehensive parts and labour or 5-years with a Zip Certified Installation |
| Chilling Technology | Air cooled technology making it 100% water efficient                                |

# Plumbing

|                           |  |
|---------------------------|--|
| Water supply requirements | Cold   |
| Water connection          | 1/2" BSP (G1/2)  |
| Water valves              | Integrated 500kPa Pressure limiting valve and Dual Check Valve |
| Water pressure            | Min 250kPa - Max 700kPa  |

# Electrical

|              |                          |
|--------------|--------------------------|
| Power rating | 1.53kW 220-240V 50Hz     |
| Power supply | 1 × 10 Amp socket outlet |

# Tap design

|                    |  |
|--------------------|--|
| Tap                | Zip HydroTap CLASSIC PLUS Tap (Brushed Gunmetal) |
| HydroTap style     | Classic Plus                                     |
| Finish             | Brushed Gunmetal                                 |
| Disability options | Unavailable                                      |

# Command centre

|            |                          |
|------------|--------------------------|
| Dimensions | W339mm x D483mm x H333mm |
|------------|--------------------------|

# Installation

## Installation requirements

1. Installation and connection of your Zip HydroTap must be carried out by a Zip Certified service technician, observing national and local regulations.
2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1 metre of the product.
3. Zip HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation.
4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service.
5. Installation by Zip Professional Service can be arranged with a phone call or through [www.zipwater.com/book-service-visit](http://www.zipwater.com/book-service-visit)

## Files

Installation Layout 3D (DWG)

BKL2 HydroTap G5 v1.2 01.2025 BCS BCS20

### Ventilation requirements

Contact your local service provider if ventilation is not suitable

#### Option 1. Cupboard with 40mm min overhang

40mm min  
50mm min clearance beside inlet  
Air exhaust cut-out  
min. 40  
300

#### Option 2. Cupboard with less than 40mm overhang

50mm min clearance beside inlet  
Floor mounting plate cut-out  
40  
300  
Air exhaust cut-out  
40  
285

### Tap Positioning

Position the Tap to dispense into the sink. Alternatively, mount on a Font, available as an accessory.

Ø35mm hole for Tap

Classic Plus tap  
Raised Font with Extension (optional accessory)  
CO<sub>2</sub> gas cylinder  
Ø105  
IEC Flex & Plug 230-240V, 50Hz power outlet  
Mains cold water isolation valve (not supplied)  
Clearance Envelope  
4mm buffer pad air space  
Clearance Envelope  
A minimum overhang or kickboard height is required for ventilation. Refer to the installation instructions.  
SCALE 1:5  
ALL DIMENSIONS IN MM UNLESS OTHERWISE SPECIFIED. INSTALLATION DIAGRAMS ARE FOR ILLUSTRATIVE PURPOSES ONLY. HOSES ARE NOT SHOWN TO SCALE AND CANNOT BE LENGTHENED.

### HydroTap Tap options

#### Classic Plus

116  
216  
126  
Ø46  
Ø35mm hole required

#### Elite Plus

110  
221  
135  
Ø46  
Ø35mm hole required

#### Raised Font with 135mm Extension Part No. 95258

240  
116  
268  
20  
351

### Cutting detail

ø10 for M6 stud  
ø86 hole for bowl  
ø35 hole for tap

## HydroTap G5 BCS Home

shown with Classic Plus tap and Raised Font (optional accessory)

Installation Layout (PDF)

# BIM files



↓ ArchiCAD Swift  
Globals Library  
(LCF)



↓ ArchiCAD Zip Water  
Library (IFC)



↓ Revit Virtual  
Showroom (RVT)

↓ Download all

# Certifications



OHS  
ISO 45001



Environment  
ISO 14001



Quality  
ISO 9001



↓ Health & Safety  
(PDF)



↓ Environment ISO  
(PDF)



↓ Quality ISO (PDF)



↓ Environmental  
Product Declaration  
Brochure (PDF)



↓ ARC (PDF)



↓ Filter performance  
(PDF)



↓ HydroTap Clean  
SDS (PDF)

# Manuals & brochures



↓ Brochure (PDF)



↓ CO<sub>2</sub> MSDS (PDF)



↓ Instruction manual (PDF)



↓ Quick guide (PDF)



↓ Tap operation label (PDF)



↓ User manual (PDF)

↓ Download all

# Accessories



95258Z1902

Font Kit Raised Brushed Gunmetal



90915Z1902

Font Kit Brushed Gunmetal