



Induction hob

HI2642FBG1

Series 2

Bridge function

Installation

Black

Construction and performance

- Frame design: Without frame
- Number of cooking zones: 4
- PowerBoost function: Yes
- Front left zone type: Square zone Real Bridge™
- Front left zone dimension: 210X190
- Front left zone power: 2100
- Front left zone boost power: 3000
- Front right zone type: Induction heater
- Front right zone dimension: 160
- Front right zone power: 1400
- Front right zone boost power: 1850
- Rear left zone type: Square zone Real Bridge™
- Rear left zone dimension: 210X190
- Rear left zone power: 2100
- Rear left zone boost power: 3000
- Rear right zone type: Induction heater
- Rear right zone dimension: 210
- Rear right zone power: 2300
- Rear right zone boost power: 3000

Use and flexibility

- Bridge function: Bridge function
- Functions-induction hob: Bridge Induction, Boiling
- Pot detection: AutoDetect

Interaction and control

- Control panel: Touch control

Design and integration

- Edges: Soft cut edges
- Min. niche width: 560
- Width of niche size for installation max.: 562
- Min. niche height: 70
- Depth (incl. wall spacing): 490
- Type of hob installation: Top & flush built-in installation

Safety and maintenance

- Residual heat indicator: Yes

Technical data

- Voltage (V): 220-240 V
- Frequency: 50-60 Hz

Dimensions

- Height: 54
- Width: 600
- Depth: 520
- Net weight: 8.701

Logistic information

- Packaging height: 200

- Packaging width: 670
- Packaging depth: 640
- Gross weight: 11.2
- Product code: 744745
- EAN code: 3838782883071

