



Induction hob

HI2842FBG1

Series 2

Bridge function

Installation

Black

Construction and performance

- Frame design: Without frame
- Number of cooking zones: 4
- PowerBoost function: Yes
- Front left zone type: Induction heater
- Front left zone dimension: 250
- Front left zone power: 2300
- Front left zone boost power: 3000
- Front right zone type: Square zone Real Bridge™
- Front right zone dimension: 210X190
- Front right zone power: 2100
- Front right zone boost power: 3000
- Cooking zone middle behind: Induction heater
- Ø middle behind (mm): 200
- Cooking zone power middle behind: 2300
- 2. cooking zone power middle behind: 3000
- Rear right zone type: Square zone Real Bridge™
- Rear right zone dimension: 210X190
- Rear right zone power: 2100
- Rear right zone boost power: 3000

Use and flexibility

- Bridge function: Bridge function
- Functions-induction hob: Bridge Induction, Boiling
- Pot detection: AutoDetect

Interaction and control

- Control panel: Touch control

Design and integration

- Edges: Soft cut edges
- Min. niche width: 750
- Width of niche size for installation max.: 752
- Min. niche height: 70
- Depth (incl. wall spacing): 490
- Type of hob installation: Top & flush built-in installation

Safety and maintenance

- Residual heat indicator: Yes

Technical data

- Voltage (V): 220-240 V
- Frequency: 50-60 Hz

Dimensions

- Height: 54
- Width: 800
- Depth: 520
- Net weight: 10

Logistic information

- Packaging height: 140

- Packaging width: 880
- Packaging depth: 590
- Gross weight: 12.2
- Product code: 744748
- EAN code: 3838782883323

