



# HYDROTAP G5 BA ELITE PLUS BRUSHED ROSE GOLD



BOILING



AMBIENT

FILTERED



## Order Code H5E785Z05AU

Zip HydroTap Design Range Boiling, Ambient, Filtered water system features a single under bench command centre including full colour interactive touch screen display with pin code protection and customisable settings including boiling water safety mode, 2 energy saving modes including ON/OFF timers and 2 hour sleep mode, SteriTouch® antimicrobial protection impregnated into key water paths for enhanced hygiene, and 0.2 micron water filtration.

Manufacturing Code H5E785Z05AU

Capacity Residential

**Tap** Zip HydroTap Design Range ELITE PLUS Tap (Brushed Rose Gold)

**Water Pressure** Min 250kPa - Max 700kPa

**Water Connection** 1/2" BSP (G1/2)

**Water Supply Requirements** Cold

**Water Valves** Integrated 500kPa Pressure limiting valve and Dual Check Valve

**Power Rating** 1.35kW 220-240V 50Hz

**Power Supply** 1 x 10 Amp socket outlet

**Dimensions** W280mm x D313mm x H333mm

**Product Approvals** WaterMark, RCM, ARC

**Warranty**

5 years (appliance warranty 36 months plus additional 24 months tank warranty)

**Installation Requirements**

1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations.
2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1 metre of the product.
3. Zip Micro is air-cooled so discrete cabinetry cut-outs are required for ventilation.
4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service.
5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit.
6. Installation by Zip Professional Service can be arranged with a phone call or through [www.zipwater.com/book-service-visit](http://www.zipwater.com/book-service-visit)

**Installation Detail**

DKL2 HydroTap G5 v1.00 02.21 B, BA

<p><b>Ventilation requirements</b> Contact your local service provider if ventilation is not suitable</p> <p><b>Clearance envelope</b> Position the Tap and the Command Centre as close together as possible.</p> <p>200 333 50 Command Centre width</p>	<p><b>HydroTap Tap options</b></p> <p>Classic Plus Elite Plus</p> <p>116 110 216 221 128 135 ø46 ø46</p>	<p><b>Font options</b></p> <p><b>Raised Font with 135mm Extension</b></p> <p>116 ø46 260 351 20 116 268</p> <p><b>Font with 135mm Extension</b></p> <p>116 ø46 260 351 6 104 ø219</p>	
<p>Air outlet louvre (if required) Cut-out in door/wall, towards the top of the cabinet</p> <p>285 60</p> <p>Air inlet cut-out (required) Cut-out in cabinet floor</p> <p>max. 43 326</p>	<p><b>Tap Positioning</b> Position the Tap to dispense into the sink, allowing clearance for a cup or teapot. Alternatively, mount the HydroTap Tap on a Font (available as an accessory).</p> <p>ø35mm hole for HydroTap Tap</p> <p>Sink</p>	<p><b>Cutting detail</b></p> <p>ø10 for M6 stud ø86 hole for bowl ø35 hole for tap</p> <p>152 116 164</p> <p><b>Cutting detail</b></p> <p>ø108 hole for bowl ø35 hole for tap</p> <p>ø10 for M6 stud 60 104 ø219</p>	

Classic Plus Tap 216

Clearance Envelope

200 min. 333

Mains cold water isolation valve (not supplied) 50 min. 280 50 min.

Air inlet grille IEC Flex & Plug 230-240V, 50Hz power outlet

4mm buffer pad air space

313

**HydroTap G5**  
**B Home, BA Home**  
shown with "Classic Plus" Tap

SCALE 1:5  
ALL DIMENSIONS IN MM UNLESS OTHERWISE SPECIFIED. INSTALLATION DIAGRAMS ARE FOR ILLUSTRATIVE PURPOSES ONLY. HOSES ARE NOT SHOWN TO SCALE AND CANNOT BE LENGTHENED.